


Shenzhen Nordson Bo Communication Co., Ltd

PRODUCT SPECIFICATION

Parameter	Units	Spec
Product Name		Clockwise SMT Circulator
Product Model		SC020SA-960-1215-100-1
Product Code		101.904.01xx
Documentation Edition		V1.0
RoHS		RoHS 2.0
Frequency Range	MHz	960-1215
Insertion loss	dB max	0.40 (Temp +25±5°C)
	dB max	0.50 (Temp -55°C~+85°C)
Isolation	dB min	22.0 (Temp +25±5°C)
	dB min	20.0 (Temp -55°C~+85°C)
Return Loss	dB min	22.0 (Temp +25±5°C)
	dB min	20.0 (Temp -55°C~+85°C)
Average power	W min	100
Peak power	W min	1000
Direction of circulation		CW
Plating		Housing: Ni1 Cu3 Ag3 PIN: Ag4
Reflow temperature	°C	260°C max for 10 seconds
Storage Temperature Range	°C	-55°C~+150°C

Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.



Shenzhen Nordson Bo Communication Co., Ltd

2nd floor, Building A, Juchuang Jingu Creative Park, Xili Xinguang Road, Nanshan District, Shenzhen
Tel: 400-049-8280 (86)0755-26701002/26701085 Fax:0755-26623329